

Points Advance slot  
 .335" = 24°  
 pin = .189

Vac Adv

.0125" = 10° crankshaft  
 .125 = 10° crankshaft  
 .150 = 12° crank

HEI

CP	Weights		
	up	139	53
346	24	23	24
349	20	19	20
361	24	22	23
363	15	14	15
364	18	16	17
365	6	6	5
368	20	19	20
369	22	20	21
370	25	24	25
375	26	24	26
389	21	19	20
393	7	7	6
398	24	24	24
399	25	23	25
400	14	13	14
402	26	25	25
404	16	15	16
406	21	20	21
416	24	23	24
417	24	25	24
422	20	19	20
432	24	23	24
438	18	17	18
444	21	20	21
445	19	18	19
446	17	16	16
449	24	23	24
451	20	19	20
452	24	22	23
459	25	23	24
462	19	18	19
469	21	20	21
470	24	23	24
481	14	13	14
482	24	23	24
485	25	23	24
486	22	21	22

CP	Weights		
	down	139	53
346	21		
349	30		
361	28		
363	21		
364	22		
365	14		
368	21		
369	24		
370	24		
375	22		
389	22		
393	17		
398	21		
399	13		
400	18		
402	24		
404	28		
406	22		
416	23		
417	15		
422	18		
432	20		
438	15		
444	17		
445	29		
446	23		
449	18		
451	22		
452	24		
459	29		
462	19		
469	21		
470	19		
481	17		
482	18		
485	15		
486	15	14	14

#  
 10 483  
 371 508  
 381 508  
 383  
 392  
 397  
 401  
 465  
 467  
 476  
 381/139 15  
 401/139 24  
 467/139 24  
 483/139 24  
 508/139 24

381/139 15  
 401 22  
 467/139 17  
 483/139 21  
 508/139 22